

TECHNICAL DATA

Article:	98610//190gr	Special Tape
Adhesive:		acrylic dispersion, solvent free, no VOC, chlorine and plasticers
Thickness:		0.26 mm
Coat weight adhesive:		190g/m ² ± 10 %
Carrier:		PE-foil green, reinforced with polyester scrim
Liner:		siliconised paper, brown
Peeling resistance	AFERA 4001	>25 N/25 mm (cohesion break)
Processing temperature:		from – 10° C
Temperature range:		- 30° up to 120 °C
Condensation water resistance:		good
Ageing resistance:		very good
Softener resistance:		very good
Adhesive characteristics:		aggressive adhesive
Shelf life:		1 year

The functionality of the products Item no 98610//190gr we declare a warranty of 10 years from application of the intended use and functional, professional and properly used tapes. This warranty expressly relates to the use of a vapor-lock brakes and to DIN 4108-7 EnEV, ÖNORM B 8110-2 and SIA 180 PE-foil with the products we produce film tape 98610// 190gr. Use in - and tolerate - "standing" water is specifically excluded.

As applications are Germany, Italy, Austria, Switzerland and Northern Europe with the currently prevailing climatic conditions and the average normal sunlight.

With respect to the recognition of a possible complaint is the professional finish to DIN 4108-7 EnEV, ÖNORM B 8110-2 and SIA 180 taking into account our current technical data sheet, a specialty certificate of in terms of craftsmanship.

Any further claims for breach of warranty are excluded.

And to degradation by external influence and pollution are not covered by the warranty. Of origin and batch number used, and evidence of appropriate and proper processing of the material is responsible in case of a complaint to the customer.