

BW

## Wood to Steel Drill Wing Screw

*The drill wing screw, which is self-drilling and can be used outdoor, is used for fitting wood battens, wood fibreboards and fibercement boards to beams and steel joists. The wings remove material to a larger diameter than regular threads and prevent the threads engaging in the material, which means there is no need for pre-drilling before fitting.*

## Ominaisuudet

### Features

- 6 lobe drive
- Ribbed flat head
- Drill point with wings
- Metal tapping thread

### Sovellus

### Liitos

- Wood to steel



### BW Wood to Steel Drill Wing Screw

## Technical Data

Mitat ja ominaisarvot



Tuotenro	Tuotenumero	Mitat [mm]				Timber thickness [mm]	Steel thickness [mm]	Bit
		l <sub>g</sub>	d	l	d <sub>h</sub>			
BW4.2X45	74258	Filetage total	4.2	45	9.5	6 - 30	1 - 2	TX25
BW4.8X50	74259	Filetage total	4.8	50	9.5	10 - 38	2 - 4	TX25
BW4.8X85	74260	Filetage total	4.8	85	9.5	10 - 60	1 - 2	TX25
BW5.5X65	74262	Filetage total	5.5	65	12.1	10 - 40	2 - 4	TX30
BW5.5X85	74263	Filetage total	5.5	85	12.1	25 - 60	2 - 4	TX30
BW5.5X90	74270	Filetage total	5.5	90	12.1	25 - 55	4 - 12	TX30
BW5.5X115	74261	Filetage total	5.5	115	12.1	40 - 80	4 - 12	TX30

BW Phosphated, Collated\*



Tuotenro	Tuotenumero	DB nr.	NOBB nr.	Mitat [mm]			Steel thickness [mm]	Bit	Qty/box
				d	l	d <sub>h</sub>			
BW3.9X42	75723	2056070	55836582	3.9	42	11.5	2	PH2	1000

\* Flat tape collated for standard auto-feed screwdrivers

