

## Tekniset tiedot

**SIMPSON**  
**Strong-Tie**

### DSPROA4 Hardwood Decking Screw - Stainless Steel A4

*Made for hardwood decking such as Cumaro, Bankirai and others. Can be used in Marine environments. Needs pre-drilling with 4 mm drill and pre-countersinking close to the edge.*

## Ominaisuudet

### Materiaali

- Stainless Steel A4

### Features:

- 6 lobe drive
- Double threaded
- Chisel point

## Sovellus


### Sovellus

- Hardwood decking boards to wood



**A4**

**SEVERE**



DSPROA4

Hardwood Decking Screw - Stainless Steel A4

## Technical Data

Mitat



Tuotenro	Article number	Mitat [mm]					Bit	Cond.	m <sup>2</sup> / box
		d	l	d <sub>h</sub>	l <sub>g1</sub>	l <sub>g2</sub>			
DSPROA45.5X50	74287	5.5	50	7	22.5	10.5	T-25	150	4.4
DSPROA45.5X60	74288	5.5	60	7	27.5	10.5	T-25	150	4.4
DSPROA45.5X70	74289	5.5	70	7	32.5	10.5	T-25	150	4.4
DSPROA45.5X80	74290	5.5	80	7	37.5	10.5	T-25	150	4.4

Tuotteen ominaisuudet

Tuotenro	Taivutuslujuus - M <sub>y,k</sub> [Nm] [Nm]	Tyypillinen vetoparametri - f <sub>ax,k,90°</sub> [N/mm <sup>2</sup> ] [N/mm <sup>2</sup> ]	Tyypillinen läpivetoparametri - f <sub>head,k</sub> [N/mm <sup>2</sup> ] [N/mm <sup>2</sup> ]	Tyypillinen vetolujuus - f <sub>tens,k</sub> [kN] [kN]	Torsional ratio
DSPROA45.5X50	7585	12.8	31.8	7.8	3.8
DSPROA45.5X60	7585	12.8	31.8	7.8	3.8
DSPROA45.5X70	7585	12.8	31.8	7.8	3.8
DSPROA45.5X80	7585	12.8	31.8	7.8	3.8

Simpson Strong-Tie / Gbo Fastening  
Systems AB  
Bruksvägen 2, 593 75 Gunnebo  
tel: 0490-300 00  
fax : 0490-233 00

Copyright by Simpson Strong-Tie®

Tämän materiaalin tiedot ovat yksinomaan Simpson Strong-Tie:n © omaisuutta

Tiedot ovat voimassa ja käytettävissä ainoastaan Simpson –Strong-Tie:n © tuotteita käytettäessä.

DSPROA4

Hardwood Decking Screw - Stainless Steel A4



www.strongtie.fi

SIMPSON

Strong-Tie®

2023-07-14