

## Tekniset tiedot

**SIMPSON**

**Strong-Tie**

FBCB

### Fibre Cement Screw, Drillpoint

*FBCB screws are used in humid conditions both indoor and outdoor. They are particularly suited for fixing fibre cement boards to steel joists with a maximum thickness of 2.0 mm.*

### Ominaisuudet

#### Materiaali

- Korroosiosuoja: Impreg<sup>®</sup>+

#### Hyödyt

- PH drive
- Countersunk head with ribs
- Drill point
- Impreg<sup>®</sup>+ coating

### Sovellus

#### Liitos

- Fibre cement to steel



FBCB  
Fibre Cement Screw, Drillpoint

## Technical Data

Mitat



Tuotenro	Item code	Mitat [mm]				Bit
		d	l	d <sub>h</sub>	t <sub>fix</sub>	
FBCB3.9X25	75456	3.9	25	6.8	15	PH2
FBCB3.9X35	75457	3.9	35	6.8	26	PH2

FBCB Collated Screws

Tuotenro	Item code	DB nr.	NOBB nr.	Mitat [mm]				Bit	Box Quantity
				d	l	d <sub>h</sub>	t <sub>fix</sub>		
FBCB3.9X25 Collated	75721	2056068	55842201	3.9	25	6.8	15	PH2	1000

\* Flat tape collated for standard auto-feed screwdrivers  
Also available Quik Drive collated

