

FBCS Fibre Cement Screw

FBCS screws are used in humid conditions both indoor and outdoor. They are particularly suited for fixing fibre cement boards to wood or steel joists with a maximum thickness of 1.0 mm.

Ominaisuudet

Materiaali

- Korroosiosuoja: Impreg[®]+


Hyödyt

- PH drive
- Countersunk head with ribs
- Sharp point
- Impreg[®]+ coating

Sovellus

Liitos

- Fibre cement to steel or wood



FBCS
Fibre Cement Screw

Technical Data

Mitat



Tuotenro	Item code	Fastener dimensions [mm]						Bit
		d	l	d _h	d ₁	l _g	t _{fix}	
FBCS3.9X25	75453	3.9	25	6.8	2.4	18	15	PH2
FBCS3.9X35	75454	3.9	35	6.8	2.4	28	26	PH2

FBCS Collated Screws

Tuotenro	Item code	DB nr.	NOBB nr.	Fastener dimensions [mm]										Bit	Box Quantity
				d	l	d _h	d ₁	A _h	h _t	l _g	l _p	t _{fix}			
FBCS3.9X25 Collated	75719	2056066	55836601	3.9	25	6.8	2.4	-	-	18	-	15	PH2	1000	
FBCS3.9X35 Collated	75720	2056067	55836597	3.9	35	6.8	2.4	-	-	28	-	26	PH2	1000	

* Flat tape collated for standard auto-feed screwdrivers
Also available Quik Drive collated

