

GK

## Drywall to Wood or Steel Screw

*GK drywall screws are used indoors for fixing drywall boards to wood battens and steel joists with a maximum thickness of 1.0 mm. The duplex head prevents the paper on the plasterboard from tearing when fastening.*

## Ominaisuudet


### Features

- PH drive
- Duplex head
- Sharp point
- High-low thread
- Electro galvanised coating

## Sovellus

### Liitos

- Drywall to timber.
- Drywall to steel.



GK  
Drywall to Wood or Steel Screw

## Technical Data

Mitat



Tuotenro	Tuotenumero	Mitat [mm]				
		d	l	d <sub>h</sub>	l <sub>g</sub>	Bit
GK3.9X30	74299	3.9	30	8	25.5	PH2
GK3.9X30 Bulk	75336	3.9	30	8	25.5	PH2
GK3.9X40	74301	3.9	40	8	35.5	PH2
GK3.9X40 Bulk	75337	3.9	40	8	35.5	PH2
GK3.9X55	74303	3.9	55	8	50.5	PH2

GK Collated Screws

Tuotenro	Tuotenumero	DB nr.	NOBB nr.	Mitat [mm]						Qty/box
				d	l	d <sub>h</sub>	d <sub>1</sub>	l <sub>g</sub>	Bit	
GK3.9X30 Collated	74296	1949826	53292377	3.9	30	8	3.2	25.5	PH2	1000
GK3.9X40 Collated	74297	1949827	53292381	3.9	40	8	3.2	35.5	PH2	1000
GK3.9X55 Collated	74298	1949828	53292396	3.9	55	8	3.2	50.5	PH2	1000

\* Flat tape collated for standard auto-feed screwdrivers

