

RST Hard Drywall to Steel Screw

RST screws are used indoors for fixing hard drywall boards to steel joists with a maximum thickness of 1.0 mm. The design of the screw with counter-threads removes enough plaster for the head to become properly countersunk in the board.

Ominaisuudet

Features

- PH drive
- Reduced bugle head
- Sharp point
- Twin thread with reverse thread
- Phosphated coating

Sovellus

Liitos

- Hard drywall/plasterboard to steel.



RST
Hard Drywall to Steel Screw

Technical Data

Mitat



Tuotenro	Tuotenumero	Mitat [mm]				
		d	l	d _h	l _g	Bit
RST3.9X32	74318	3.9	32	6.4	22	PH2
RST3.9X41	74319	3.9	41	6.4	31	PH2
RST4.2X57	74320	4.2	57	6.4	31	PH2

RST Collated Screws

Tuotenro	Tuotenumero	DB nr.	NOBB nr.	Mitat [mm]						Qty/box
				d	l	d _h	d ₁	l _g	Bit	
RST3.9X25 Collated	74321	1949848	53292752	3.9	25	6.4	2.5	15	PH2	1000
RST3.9X32 Collated	74322	1949849	53292763	3.9	32	6.4	2.5	22	PH2	1000
RST3.9X41 Collated	74323	1949850	53292778	3.9	41	6.4	2.5	31	PH2	1000
RST4.2X57 Collated	74324	1949851	53292782	4.2	57	6.4	2.9	31	PH2	1000

* Flat tape collated for standard auto-feed screwdrivers

