

TTFA4 Decking Screw - Stainless Steel A4

Suitable for marine environments and industrial atmospheres. The TTFA4 screw will not discolour the woodwork around the screw head. Also suitable for precious woods such as oak, cedar or larch.

The screw has a 6 lobe recess to ensure good grip and a cutpoint, which effectively drives the screw into the woodwork and counteracts splitting.

Ominaisuudet

Features

- 6 lobe drive.
- Flat head with nibs.
- Coarse thread.
- Type 17 point.
- Marine grade stainless steel (A4).

Sovellus

Liitos

- Decking to timber.
- Precious woods including oak, cedar and larch.



TTFA4 Decking Screw - Stainless Steel A4

Technical Data

Mitat ja ominaisarvot



Tuotenro	Tuotenumero	Mitat [mm]					
		d	l	d _h	l _g	t _{fix}	Bit
TTFA44.2X35T-20	74385	4.2	35	7	20	14	T-20
TTFA44.2X45T-20	74386	4.2	45	7	23	22	T-20
TTFA44.2X55T-20	74387	4.2	55	7	27.5	27.5	T-20
TTFA44.2X55T-20 Bulk	74388	4.2	55	7	27.5	27.5	T-20
TTFA44.8X75T-20	74389	4.8	75	7	35	40	T-20



Collated screws

Tuotenro	Tuotenumero	DB nr.	NOBB nr.	Mitat [mm]						Box Quantity	
				d	l	d _h	d ₁	l _g	t _{fix}		Bit
TTFA44.2X45PH2	74291	1949809	53293622	4.2	45	7	2.6	23	22	PH2	1000
TTFA44.2X55PH2	74292	1949810	53293637	4.2	55	7	2.6	27.5	27.5	PH2	1000

Tuotteen ominaisuudet



Tuotenro	Tuotteen ominaisuudet			
	Taivutuslujuus - M _{y,k} [M _{y,k}] [Nmm]	Tyypillinen vetoparametri - f _{ax,k,90°} [f _{ax,k,90°}] [N/mm ²]	Tyypillinen läpivetoparametri - f _{head,k} [f _{head,k}] [N/mm ²]	Tyypillinen vetolujuus - f _{tens,k} [f _{tens,k}] [kN]
TTFA44.2X35T-20	2575	17	20.4	4.2
TTFA44.2X45T-20	2575	17	20.4	4.2
TTFA44.2X55T-20	2575	17	20.4	4.2
TTFA44.2X55T-20 Bulk	2575	17	20.4	4.2
TTFA44.8X75T-20	4371	20.7	16.4	5.6
TTFA44.2X45PH2	2575	17	20.4	4.2
TTFA44.2X55PH2	2575	17	20.4	4.2

