

Tekniset tiedot

SIMPSON

Strong-Tie

TTSFS

Countersunk Wood Screw - Stainless Steel A4

Suitable for exterior use, the TTSFS screw has a serrated thread to reduce the resistance when driving. It has a type 17 point which prevents wood splitting. 80 mm or longer variants have an additional milling thread to further reduce the resistance.

Ominaisuudet

Features

- 6 lobe drive.
- Flat head with facet.
- Type 17 point.
- Coarse, serrated thread.
- Stainless steel.

Sovellus

Liitos

- Puu-puu liitos



TTSFS
Countersunk Wood Screw - Stainless Steel A4

Technical Data

Mitat ja ominaisarvot



Tuotenro	Tuotenumero	Mitat [mm]					
		d	l	d _h	l _g	t _{fix}	Bit
TTSFS5.0X60	74446	5	60	9.5	32	28	T-25
TTSFS5.0X70	74447	5	70	9.5	35	35	T-25
TTSFS5.0X80	74448	5	80	9.5	40	40	T-25
TTSFS5.0X90	74449	5	90	9.5	45	45	T-25
TTSFS5.0X100	74444	5	100	9.5	55	45	T-25
TTSFS5.0X120	74445	5	120	9.5	60	60	T-25
TTSFS6.0X70	74473	6	70	11.6	35	35	T-30
TTSFS6.0X80	74474	6	80	11.6	40	40	T-30
TTSFS6.0X90	74475	6	90	11.6	45	45	T-30
TTSFS6.0X100	74450	6	100	11.6	55	45	T-30
TTSFS6.0X120	74471	6	120	11.6	60	60	T-30
TTSFS6.0X140	74472	6	140	11.6	65	75	T-30

Tuotteen ominaisuudet

Tuotenro	Taivutuslujuus - M _{y,k} [Nmm]	Tyypillinen vetoparametri - f _{ax,k,90°} [N/mm ²]	Tyypillinen läpivetoparametri - f _{head,k} [N/mm ²]	Tyypillinen vetolujuus - f _{tens,k} [kN]
TTSFS5.0X60	4710	14.9	16	6.3
TTSFS5.0X70	4710	14.9	16	6.3
TTSFS5.0X80	4710	14.9	16	6.3
TTSFS5.0X90	4710	14.9	16	6.3
TTSFS5.0X100	4710	14.9	16	6.3
TTSFS5.0X120	4710	14.9	16	6.3
TTSFS6.0X70	8570	13.6	16.2	9.5
TTSFS6.0X80	8570	13.6	16.2	9.5
TTSFS6.0X90	8570	13.6	16.2	9.5
TTSFS6.0X100	8570	13.6	16.2	9.5
TTSFS6.0X120	8570	13.6	16.2	9.5
TTSFS6.0X140	8570	13.6	16.2	9.5

