

## Tekniset tiedot

**SIMPSON**

**Strong-Tie**

TTUFP

### Pan Head Wood Screw

*TTUFP screws have a 6 lobe drive and type 17 point which drives the screw smoothly into the woodwork and prevents splitting. All screws have saw thread that reduces torque. Serrations under the head help the screw to grip the material.*

### Ominaisuudet

#### Features

- 6 lobe point
- Pan head
- Type 17 point
- Serrated thread and milling thread
- Electro galvanised coating

### Sovellus

#### Liitos

- Puu-puu liitos
- Steel to wood



## TTUFP Pan Head Wood Screw

### Technical Data

Mitat ja ominaisarvot



Tuotenro	Tuotenumero	NOBB nr.	Mitat [mm]				
			d	l	d <sub>h</sub>	l <sub>g</sub>	Bit
TTUFP3.0X15*	74511	53294496	3	15	5.5	15	T-10
TTUFP3.0X20*	74513	53294500	3	20	5.5	20	T-10
TTUFP3.5X15*	74512	53294515	3.5	15	6.6	15	T-15
TTUFP3.5X20*	74514	53294526	3.5	20	6.6	20	T-15
TTUFP3.5X25*	74515	53294534	3.5	25	6.6	25	T-15
TTUFP3.5X30*	74517	53294545	3.5	30	6.6	30	T-15
TTUFP4.0X15*	74518	53294553	4	15	7.6	15	T-20
TTUFP4.0X20*	74519	53294564	4	20	7.6	20	T-20
TTUFP4.0X25*	74520	53294572	4	25	7.6	25	T-20
TTUFP4.0X30*	74521	53294583	4	30	7.6	30	T-20
TTUFP4.0X35*	74522	53294598	4	35	7.6	35	T-20
TTUFP4.0X40*	74523	53294602	4	40	7.6	40	T-20
TTUFP4.0X50*	74524	53294617	4	50	7.6	30	T-20
TTUFP5.0X30	74525	53294621	5	30	9.7	26	T-25
TTUFP5.0X40	74526	53294636	5	40	9.7	36	T-25
TTUFP5.0X50	74527	53294640	5	50	9.7	30	T-25
TTUFP5.0X60	74528	53294655	5	60	9.7	35	T-25
TTUFP5.0X70	74529	53294666	5	70	9.7	40	T-25
TTUFP5.0X80	74530	53294674	5	80	9.7	50	T-25
TTUFP6.0X40	74532	53294693	6	40	11.7	35	T-30
TTUFP6.0X50	74533	53294704	6	50	11.7	30	T-30
TTUFP6.0X60	74534	53294712	6	60	11.7	35	T-30
TTUFP6.0X70	74535	53294723	6	70	11.7	40	T-30
TTUFP6.0X80	74536	53294738	6	80	11.7	50	T-30
TTUFP6.0X100	74531	53294685	6	100	11.7	60	T-30

\* not covered by CE marking

## TTUFP Pan Head Wood Screw

### Tuotteen ominaisuudet

Tuotenro	Tuotteen ominaisuudet			
	Taivutuslujuus - $M_{y,k}$ [ $M_{y,k}$ ] [Nmm]	Tyypillinen vetoparametri - $f_{ax,k,90^\circ}$ [ $f_{ax,k,90^\circ}$ ] [N/mm <sup>2</sup> ]	Tyypillinen läpivetoparametri - $f_{head,k}$ [ $f_{head,k}$ ] [N/mm <sup>2</sup> ]	Tyypillinen vetolujuus - $f_{tens,k}$ [ $f_{tens,k}$ ] [kN]
TTUFP5.0X30	6720	15	16.9	7.9
TTUFP5.0X40	6720	15	16.9	7.9
TTUFP5.0X50	6720	15	16.9	7.9
TTUFP5.0X60	6720	15	16.9	7.9
TTUFP5.0X70	6720	15	16.9	7.9
TTUFP5.0X80	6720	15	16.9	7.9
TTUFP6.0X40	9500	12.5	17.4	11.1
TTUFP6.0X50	9500	12.5	17.4	11.1
TTUFP6.0X60	9500	12.5	17.4	11.1
TTUFP6.0X70	9500	12.5	17.4	11.1
TTUFP6.0X80	9500	12.5	17.4	11.1
TTUFP6.0X100	9500	12.5	17.4	11.1

