

TTUFS

Countersunk Wood Screw - Electro Galvanised

Suitable for interior use, the TTUFS screw has a serrated thread to reduce the resistance when driving. It has a type 17 point which prevents wood splitting. 80 mm or longer variants have an additional milling thread to further reduce the resistance.

Ominaisuudet

Features

- 6 lobe drive
- Prismatic countersunk head design ensures a flush finish
- Type 17 point
- Serrated thread
- Electro galvanised

Sovellus

Use on

-




TTUFS

Countersunk Wood Screw - Electro Galvanised

Technical Data

TTUFS Countersunk Wood Screw - Electro Galvanised

Mitat ja ominaisarvot



Tuotenro	Item Nr.	Mitat [mm]				
		d	l	d _h	l _g	Bit
TTUFS3.0X16	74414	3	16	6	11	T-10
TTUFS3.0X20	74415	3	20	6	15	T-10
TTUFS3.0X25	74416	3	25	6	20	T-10
TTUFS3.0X30	74417	3	30	6	25	T-10
TTUFS3.0x40	77606	3	40	6	-	T-10
TTUFS3.5X16	74418	3.5	16	7	11	T-15
TTUFS3.5X20	74419	3.5	20	7	15	T-15
TTUFS3.5X25	74420	3.5	25	7	20	T-15
TTUFS3.5X30	74421	3.5	30	7	25	T-15
TTUFS3.5X35	74422	3.5	35	7	30	T-15
TTUFS3.5X40	74423	3.5	40	7	35	T-15
TTUFS3.5X50 PT	74424	3.5	50	7	30	T-15
TTUFS3.5X50 FT	77609	3.5	50	7	30	T-15
TTUFS4.0X20	74425	4	20	8	15	T-20
TTUFS4.0X25	74426	4	25	8	20	T-20
TTUFS4.0X30 PT	77610	4	25	8	20	T-20
TTUFS4.0X30 FT	74427	4	30	8	25	T-20
TTUFS4.0X35	74428	4	35	8	30	T-20
TTUFS4.0X40 PT	77612	4	40	8	35	T-20
TTUFS4.0X40 FT	74429	4	40	8	35	T-20
TTUFS4.0X45 PT	74430	4	45	8	29	T-20
TTUFS4.0X45 FT	77613	4	45	8	29	T-20
TTUFS4.0X50 PT	74431	4	50	8	30	T-20
TTUFS4.0X50 FT	77615	4	50	8	30	T-20
TTUFS4.0X60 PT	74432	4	60	8	35	T-20
TTUFS4.0X60 FT	77616	4	60	8	35	T-20
TTUFS4.0X70	74433	4	70	8	40	T-20
TTUFS4.5X25	74434	4.5	25	8.4	20	T-20
TTUFS4.5X30	74435	4.5	30	8.4	25	T-20
TTUFS4.5X35 PT	77617	4.5	35	8.4	30	T-20
TTUFS4.5X35 FT	74436	4.5	35	8.4	30	T-20
TTUFS4.5X40 PT	77618	4.5	40	8.4	35	T-20
TTUFS4.5X40 FT	74437	4.5	40	8.4	35	T-20
TTUFS4.5X45 PT	74438	4.5	45	8.4	29	T-20
TTUFS4.5X45 FT	77619	4.5	45	8.4	29	T-20
TTUFS4.5X50 PT	74439	4.5	50	8.4	30	T-20
TTUFS4.5X50 FT	77620	4.5	50	8.4	30	T-20

Diameters 3.0, 3.5 and 4.0 screws are not CE marked.

TTUFS Countersunk Wood Screw - Electro Galvanised

Tuotenro	Item Nr.	Mitat [mm]				
		d	l	d _h	l _g	Bit
TTUFS4.5X60 PT	74440	4.5	60	8.4	35	T-20
TTUFS4.5X60 FT	77627	4.5	60	8.4	35	T-20
TTUFS4.5X70	74441	4.5	70	8.4	40	T-20
TTUFS4.5X80	74442	4.5	80	8.4	50	T-20
TTUFS5.0X30	74373	5	30	9.5	25	T-25
TTUFS5.0x35	77629	5	35	9.5	30	T-25
TTUFS5.0X40 PT	77630	5	40	9.5	35	T-25
TTUFS5.0X40 FT	74374	5	40	9.5	35	T-25
TTUFS5.0x45	77631	5	45	9.5	40	T-25
TTUFS5.0X50 PT	74375	5	50	9.5	30	T-25
TTUFS5.0X50 FT	77634	5	50	9.5	30	T-25
TTUFS5.0X60 PT	74376	5	60	9.5	35	T-25
TTUFS5.0X60 FT	77635	5	60	9.5	35	T-25
TTUFS5.0X70	74377	5	70	9.5	40	T-25
TTUFS5.0X80	74378	5	80	9.5	40	T-25
TTUFS5.0X90	74379	5	90	9.5	45	T-25
TTUFS5.0X90 Bulk	75500	5	90	9.5	45	T-25
TTUFS5.0X100	74443	5	100	9.5	60	T-25
TTUFS5.0X120	74372	5	120	9.5	60	T-25
TTUFS6.0x30	77636	6	30	11.6	24	T-30
TTUFS6.0X40	74455	6	40	11.6	34	T-30
TTUFS6.0X50 PT	74457	6	50	11.6	30	T-30
TTUFS6.0X50 FT	77637	6	50	11.6	30	T-30
TTUFS6.0X60 PT	74458	6	60	11.6	35	T-30
TTUFS6.0X60 FT	77638	6	60	11.6	35	T-30
TTUFS6.0X70	74459	6	70	11.6	40	T-30
TTUFS6.0X80	74460	6	80	11.6	40	T-30
TTUFS6.0X90	74461	6	90	11.6	45	T-30
TTUFS6.0X100	74380	6	100	11.6	60	T-30
TTUFS6.0X120	74451	6	120	11.6	70	T-30
TTUFS6.0X140	74452	6	140	11.6	70	T-30
TTUFS6.0X160	74453	6	160	11.6	70	T-30
TTUFS6.0X180	74454	6	180	11.6	70	T-30

Diameters 3.0, 3.5 and 4.0 screws are not CE marked.

TTUFS Countersunk Wood Screw - Electro Galvanised

Tuotteen ominaisuudet

Tuotenro	Taivutuslujuus - $M_{y,k}$ [Nmm]	Tyypillinen vetoparametri - $f_{ax,k,90^\circ}$ [N/mm ²]	Tyypillinen läpivetoparametri - $f_{head,k}$ [N/mm ²]	Tyypillinen vetolujuus - $f_{tens,k}$ [kN]
TTUFS3.0X16	-	-	-	-
TTUFS3.0X20	-	-	-	-
TTUFS3.0X25	-	-	-	-
TTUFS3.0X30	-	-	-	-
TTUFS3.0x40	-	-	-	-
TTUFS3.5X16	-	-	-	-
TTUFS3.5X20	-	-	-	-
TTUFS3.5X25	-	-	-	-
TTUFS3.5X30	-	-	-	-
TTUFS3.5X35	-	-	-	-
TTUFS3.5X40	-	-	-	-
TTUFS3.5X50 PT	-	-	-	-
TTUFS3.5X50 FT	-	-	-	-
TTUFS4.0X20	-	-	-	-
TTUFS4.0X25	-	-	-	-
TTUFS4.0X30 PT	-	-	-	-
TTUFS4.0X30 FT	-	-	-	-
TTUFS4.0X35	-	-	-	-
TTUFS4.0X40 PT	-	-	-	-
TTUFS4.0X40 FT	-	-	-	-
TTUFS4.0X45 PT	-	-	-	-
TTUFS4.0X45 FT	-	-	-	-
TTUFS4.0X50 PT	-	-	-	-
TTUFS4.0X50 FT	-	-	-	-
TTUFS4.0X60 PT	-	-	-	-
TTUFS4.0X60 FT	-	-	-	-
TTUFS4.0X70	-	-	-	-
TTUFS4.5X25	4660	14.7	15.6	7.8
TTUFS4.5X30	4660	14.7	15.6	7.8
TTUFS4.5X35 PT	-	-	-	-
TTUFS4.5X35 FT	4660	14.7	15.6	7.8
TTUFS4.5X40 PT	-	-	-	-
TTUFS4.5X40 FT	4660	14.7	15.6	7.8
TTUFS4.5X45 PT	4660	14.7	15.6	7.8
TTUFS4.5X45 FT	-	-	-	-
TTUFS4.5X50 PT	4660	14.7	15.6	7.8
TTUFS4.5X50 FT	-	-	-	-

Refer to relevant ITTR or ETA for more details

TTUFS
Countersunk Wood Screw - Electro Galvanised

Tuotenumero	Taivutuslujuus - $M_{y,k}$ [Nmm]	Tyypillinen vetoparametri - $f_{ax,k,90^\circ}$ [N/mm ²]	Tyypillinen läpivetoparametri - $f_{head,k}$ [N/mm ²]	Tyypillinen vetolujuus - $f_{tens,k}$ [kN]
TTUFS4.5X60 PT	4660	14.7	15.6	7.8
TTUFS4.5X60 FT	-	-	-	-
TTUFS4.5X70	4660	14.7	15.6	7.8
TTUFS4.5X80	4660	14.7	15.6	7.8
TTUFS5.0X30	6720	15	17.1	7.9
TTUFS5.0x35	-	-	-	-
TTUFS5.0X40 PT	-	-	-	-
TTUFS5.0X40 FT	6720	15	17.1	7.9
TTUFS5.0x45	-	-	-	-
TTUFS5.0X50 PT	6720	15	17.1	7.9
TTUFS5.0X50 FT	-	-	-	-
TTUFS5.0X60 PT	6720	15	17.1	7.9
TTUFS5.0X60 FT	-	-	-	-
TTUFS5.0X70	6720	15	17.1	7.9
TTUFS5.0X80	6720	15	17.1	7.9
TTUFS5.0X90	6720	15	17.1	7.9
TTUFS5.0X90 Bulk	6720	15	17.1	7.9
TTUFS5.0X100	6720	15	17.1	7.9
TTUFS5.0X120	6720	15	17.1	7.9
TTUFS6.0x30	-	-	-	-
TTUFS6.0X40	9500	12.5	16.6	11.1
TTUFS6.0X50 PT	9500	12.5	16.6	11.1
TTUFS6.0X50 FT	-	-	-	-
TTUFS6.0X60 PT	9500	12.5	16.6	11.1
TTUFS6.0X60 FT	-	-	-	-
TTUFS6.0X70	9500	12.5	16.6	11.1
TTUFS6.0X80	9500	12.5	16.6	11.1
TTUFS6.0X90	9500	12.5	16.6	11.1
TTUFS6.0X100	9500	12.5	16.6	11.1
TTUFS6.0X120	9500	12.5	16.6	11.1
TTUFS6.0X140	9500	12.5	16.6	11.1
TTUFS6.0X160	9500	12.5	16.6	11.1
TTUFS6.0X180	9500	12.5	16.6	11.1

Refer to relevant ITTR or ETA for more details

Simpson Strong-Tie / Gbo Fastening
Systems AB
Bruksvägen 2, 593 75 Gunnebo
tel: 0490-300 00
fax : 0490-233 00

Copyright by Simpson Strong-Tie®

Tämän materiaalin tiedot ovat yksinomaan Simpson Strong-Tie:n © omaisuutta

Tiedot ovat voimassa ja käytettävissä ainoastaan Simpson -Strong-Tie:n © tuotteita käytettäessä.

TTUFS
Countersunk Wood Screw - Electro
Galvanised



2023-07-15

www.strongtie.fi