

TTZNFP

Pan Head Wood Screw - Impreg®+

Suitable for exterior use, the TTZNFP screw has a serrated thread to reduce the resistance when driving. It has a Type 17 which prevents splitting.

Ominaisuudet


Features

- 6 lobe drive.
- Pan head.
- Type 17 point.
- Serrated thread.
- Impreg®+.

Sovellus

Liitos

- Puu-puu liitos
- Steel to wood



TTZNFP
Pan Head Wood Screw - Impreg®+

Technical Data

Mitat ja ominaisarvot



Tuotenro	Tuotenumero	Mitat [mm]				
		d	l	d _h	l _g	Bit
TTZNFP4.0X30*	74537	4	30	8	30	T-20
TTZNFP4.0X40*	74538	4	40	8	40	T-20
TTZNFP4.0X50*	74539	4	50	8	30	T-20
TTZNFP5.0X40	74540	5	40	9.7	36	T-25
TTZNFP5.0X50	74541	5	50	9.7	30	T-25
TTZNFP5.0X60	74542	5	60	9.7	35	T-25
TTZNFP5.0X70	74543	5	70	9.7	40	T-25

* not covered by CE marking

Tuotteen ominaisuudet

Tuotenro	Tuotteen ominaisuudet			
	Taivutuslujuus - M _{y,k} [M _{y,k}] [Nmm]	Tyypillinen vetoparametri - f _{ax,k,90°} [f _{ax,k,90°}] [N/mm ²]	Tyypillinen läpivetoparametri - f _{head,k} [f _{head,k}] [N/mm ²]	Tyypillinen vetolujuus - f _{tens,k} [f _{tens,k}] [kN]
TTZNFP5.0X40	6720	15	16.9	7.9
TTZNFP5.0X50	6720	15	16.9	7.9
TTZNFP5.0X60	6720	15	16.9	7.9
TTZNFP5.0X70	6720	15	16.9	7.9

Refer to relevant ITTR or ETA for more details

