

Tekniset tiedot

SIMPSON

Strong-Tie

UGSB

Exterior Sheathing to Steel Screw - Drill Point

Suitable for exterior use, UGSB screw can be used to fix sheathing board to steel (up to 2.0 mm thickness). The head is suited to the requirements of fitting exterior plasterboard.

Ominaisuudet

Features

- Cross point drive.
- Extended bugle head.
- Drill point.
- Metal tapping thread.
- Protec coating.

Sovellus

Suitable for

- Drywall/Wind board to Steel.



UGSB
Exterior Sheathing to Steel Screw - Drill Point

Technical Data

Mitat ja ominaisarvot



Tuotenro	Tuotenumero	Mitat [mm]			
		d	l	d _h	Bit
UGSB3.9X25	74312	3.8	25	8.9	PH2
UGSB3.9X25 Bulk	75499	3.8	25	8.9	PH2

UGSB Collated Screws

Tuotenro	Tuotenumero	DB nr.	NOBB nr.	Mitat [mm]						Qty/box
				d	l	d _h	d ₁	l _g	Bit	
UGSB3.9X25 Collated	74309	1949836	53292324	3.8	25	8.9	3.2	-	PH2	1000

* Flat tape collated for standard auto-feed screwdrivers

